

# ACCESSORIES

## DBRY-6

### MODELS

- DBRY100: Bulk 100 connectors (100 tubes loose in box, plus inner box with 100 wire nuts)
- DBRY2X25: 25 x 2-packs (2 tubes and wire nuts in a plastic bag, x 25 units)

### Features

- UL Listed for 600 Volts direct burial
- Improved red-and-yellow wire nut, eliminating the need for two different sizes
- A snap-lock feature that secures the wire nut in the bottom of the light blue waterproof tube
- 3 wire exit cutouts in the strain relief cap, to ease wire routing
- Meets Directive 2006/95/EC and IEC standards EN61984:2009, EN60998-1:2004, and EN60998-2-4:2005



### Waterproof Wire Connectors

DBRY100, DBRY2X25



### HCV

Overall height: 7.5 cm

## HCV

### Models

- HC-50F-50F: ½" Female inlet x ½" Female outlet
- HC-50F-50M: ½" Female inlet x ½" Male outlet
- HC-75F-75M: ¾" Female inlet x ¾" Male outlet

### Features

- Adjustment access from top of valve
- Adjusts to compensate for elevational changes up to 11 m: Maximum flexibility
- Variety of inlet and outlet options: Reduces need for additional fittings
- Meets schedule 80 specifications: Durable under high pressure

*Pressure loss charts for HCV products on page 210*



## HUNTER SPIRAL BARB ELBOWS

### Models

- HSBE-050: ½" male x spiral barb elbow
- HSBE-075: ¾" male x spiral barb elbow
- HSBE TOOL: Insert tool

### Features

- For use with FLEX<sub>SG</sub> Tubing
- Acetal material for sharp barbs
- Operating pressure up to 5.5 bar; 550 kPa
- Compatible with FLEX<sub>SG</sub> and other brands

### Spiral Barb Elbows

HSBE-TOOL, HSBE-050, HSBE-075



### FLEX<sub>SG</sub> Tubing

30 m and 45 cm pre-cut lengths

## FLEX<sub>SG</sub> TUBING

### Models

- FLEX<sub>SG</sub>: 30 m roll
- FLEX<sub>SG</sub>-18: 45 cm pre-cut lengths

### Features

- Engineered to resist kinking
- Inside diameter: 1.2 cm
- Operating pressure: up to 5.5 bar; 550 kPa
- Linear low-density polyethylene material