

B SERIES

Models: **G80B**
 Radius: **20.4 to 26.8 m**
 Flow: **5.11 to 13.15 m³/hr; 85.2 to 219.2 l/min**

FEATURES

- Full circle opposing nozzles
- Colour-coded nozzles: 7 standard trajectory (25°)
- Nozzle range: #23 to #53
- Exclusive PressurePort™ nozzle technology
- Water lubricated gear-drives
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- Radius: 20.4 to 26.8 m
- Flow: 5.11 to 13.15 m³/hr; 85.2 to 219.2 l/min
- Pressure range: 4.5 to 6.9 bar; 450 to 690 kPa
- All B Series rotors are pressure rated at 10 bar; 1,000 kPa



G80B
 Pop-up height: 8 cm
 Overall height: 24.5 cm
 Flange diameter: 13.7 cm
 Female Inlet: 1/4" ACME

GOLF ROTORS

G80B – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Valve Options	3 Nozzle	4 Options*
G80 = Full Circle	B = Block rotor with check valve	23 to 53 = Installed G80 Nozzle* * SSU = #23, #25 or #48	S = SSU* * Standard Stocking Unit

Example:
 G80 - B - 25 - S = G80 full circle block rotor, installed #25 nozzle, standard stocking unit model

G80B NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
23 ● Green	4.5	450	20.4	5.11	85.2	12.3	14.1
	4.8	480	21.0	5.43	90.5	12.3	14.2
	5.5	550	21.6	5.91	98.4	12.6	14.6
	6.2	620	21.9	6.34	105.6	13.2	15.2
	6.9	690	22.3	6.77	112.8	13.7	15.8
25 ● Blue	4.5	450	21.6	6.54	109.0	14.0	16.1
	4.8	480	22.3	6.79	113.2	13.7	15.8
	5.5	550	22.6	7.29	121.5	14.3	16.5
	6.2	620	22.9	7.79	129.8	14.9	17.2
	6.9	690	23.2	8.18	136.3	15.2	17.6
33 ● Grey	4.5	450	22.3	7.04	117.3	14.2	16.4
	4.8	480	22.6	7.31	121.9	14.4	16.6
	5.5	550	23.2	7.88	131.4	14.7	17.0
	6.2	620	23.5	8.40	140.1	15.3	17.6
	6.9	690	23.8	8.81	146.9	15.6	18.0
38 ● Red	4.5	450	23.2	7.97	132.9	14.9	17.2
	4.8	480	23.5	8.25	137.4	15.0	17.3
	5.5	550	24.1	8.75	145.7	15.1	17.4
	6.2	620	24.4	9.20	153.3	15.5	17.9
	6.9	690	24.7	9.75	162.4	16.0	18.5
43 ● Dk. Brown	4.5	450	23.8	8.90	148.4	15.8	18.2
	4.8	480	24.1	9.27	154.4	16.0	18.5
	5.5	550	25.0	9.93	165.4	15.9	18.3
	6.2	620	25.3	10.56	176.0	16.5	19.1
	6.9	690	25.6	11.09	184.7	16.9	19.5
48 ● Dk. Green	4.5	450	25.0	9.95	165.8	15.9	18.4
	4.8	480	25.3	10.52	175.3	16.4	19.0
	5.5	550	25.9	11.13	185.5	16.6	19.1
	6.2	620	26.2	11.79	196.5	17.2	19.8
	6.9	690	26.5	12.36	205.9	17.6	20.3
53 ● Dk. Blue	4.5	450	25.3	10.65	177.5	16.6	19.2
	4.8	480	25.6	11.15	185.9	17.0	19.6
	5.5	550	26.5	11.95	199.1	17.0	19.6
	6.2	620	26.8	12.45	207.4	17.3	20.0
	6.9	690	26.8	13.15	219.2	18.3	21.1

G80B NOZZLES



* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

G80B



B SERIES

Models: **G84B & G85B**
 Radius: **13.1 to 28.3 m**
 Flow: **1.86 to 13.24 m³/hr; 31.0 to 220.6 l/min**

FEATURES

- Models:
 - G84B: Full circle opposing nozzles
 - G85B: True full circle/adjustable part circle (60° to 360°)
- QuickCheck™ arc mechanism (G85B)
- QuickSet-360 arc mechanism (G85B)
- Dual trajectory colour-coded nozzles:
 - G84B: 10 standard trajectory (22.5°)
 - G85B: 12 standard trajectory (22.5°)
- G84B & G85B: 9 low-angle trajectory (15°)
- Nozzle range:
 - G84B: #15 to #53
 - G85B: #10 to #53
- Exclusive PressurePort™ nozzle technology
- Contour “Back-Nozzle” capabilities (G85B)
- Ratcheting stainless steel riser
- Water lubricated gear-drives
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- G84B
 - Radius: 14.9 to 28.3 m
 - Flow: 3.28 to 13.24 m³/hr; 54.6 to 220.6 l/min
 - Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- G85B
 - Radius: 13.1 to 27.7 m
 - Flow: 1.86 to 13.06 m³/hr; 31,0 to 217.7 l/min
 - Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- All B Series rotors are pressure rated at 10 bar; 1,000 kPa



G84B
 Pop-up height: 9.5 cm
 Overall height: 24.5 cm
 Flange diameter: 13.7 cm
 Female Inlet: 1¼" ACME



G85B
 Pop-up height: 9.5 cm
 Overall height: 24.5 cm
 Flange diameter: 13.7 cm
 Female Inlet: 1¼" ACME

G84B & G85B - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Valve Options	3 Nozzle	4 Options*
G84 = Full Circle	B = Block rotor with check valve	15 to 53 = Installed G84 Nozzle* * SSU = #18, #25 & #48	S = SSU* * Standard Stocking Unit
G85 = Full/Part Circle 60° - 360°	B = Block rotor with check valve	10 to 53 = Installed G85 Nozzle** ** SSU = #18, #25 & #48	S = SSU* * Standard Stocking Unit

Example:
G84 - B - 25 - S = G80 full circle block rotor, installed #25 nozzle, standard stocking unit model

GOLF ROTORS

G84B NOZZLE PERFORMANCE DATA*

Nozzle Set			Pressure		Radius	Flow		Precip mm/hr	
			bar	kPa	m	m ³ /hr	l/min	■	▲
● Tan 803611	○ 15 White	● Grey 315317	3.4	340	14.9	3.28	54.6	14.7	17.0
			4.1	410	15.5	3.65	60.8	15.1	17.4
			4.5	450	15.9	3.81	63.5	15.2	17.5
			4.8	480	16.2	3.90	65.1	15.0	17.3
5.5	550	16.8	4.13	68.9	14.7	17.0			
● Tan 803611	○ 18 Orange	● Grey 315317	3.4	340	16.8	3.97	66.1	14.1	16.3
			4.1	410	17.1	4.28	71.3	14.7	17.0
			4.5	450	17.4	4.45	74.1	14.7	17.0
			4.8	480	18.0	4.66	77.6	14.4	16.6
5.5	550	18.6	4.94	82.4	14.3	16.5			
● Tan 803611	○ 20 Brown	● Grey 315317	3.4	340	17.4	3.91	65.2	13.0	15.0
			4.1	410	18.6	4.28	71.3	12.4	14.3
			4.5	450	18.9	4.47	74.4	12.5	14.4
			4.8	480	19.2	4.67	77.9	12.7	14.6
5.5	550	19.5	5.02	83.6	13.2	15.2			
● Tan 803611	○ 23 Green	● Lt. Blue 315311	3.4	340	19.2	4.49	74.8	12.2	14.1
			4.1	410	19.8	4.99	83.2	12.7	14.7
			4.5	450	20.1	5.19	86.5	12.8	14.8
			4.8	480	20.4	5.41	90.1	13.0	15.0
5.5	550	20.4	5.81	96.9	13.9	16.1			
● Tan 803611	○ 25 Blue	● Lt. Blue 315311	4.5	450	21.6	6.50	108.3	13.9	16.0
			4.8	480	22.3	6.75	112.5	13.6	15.7
			5.5	550	22.6	7.19	119.8	14.1	16.3
			6.2	620	22.9	7.65	127.5	14.6	16.9
6.9	690	22.9	8.12	135.3	15.5	17.9			
● Tan 803611	○ 33 Grey	● Lt. Blue 315311	4.5	450	22.3	7.02	117.0	14.2	16.4
			4.8	480	22.9	7.30	121.7	14.0	16.1
			5.5	550	23.2	7.81	130.1	14.6	16.8
			6.2	620	23.5	8.24	137.3	15.0	17.3
6.9	690	24.1	8.65	144.1	14.9	17.2			
● Tan 803611	○ 38 Red	● Lt. Blue 315311	4.5	450	22.9	7.96	132.6	15.2	17.6
			4.8	480	23.2	8.29	138.1	15.4	17.8
			5.5	550	23.8	8.85	147.5	15.7	18.1
			6.2	620	24.1	9.38	156.3	16.2	18.7
6.9	690	25.0	9.87	164.4	15.8	18.2			
● Tan 803611	○ 43 Dk. Brown	● Blue 315300	-	-	-	-	-	-	-
			5.5	550	25.3	9.85	164.1	15.4	17.8
			6.2	620	25.9	10.52	175.3	15.7	18.1
			6.9	690	26.5	11.04	183.9	15.7	18.1
● Dk. Brown 803610	○ 48 Dk. Green	● Dk. Blue 833500	-	-	-	-	-	-	-
			5.5	550	25.9	10.88	181.2	16.2	18.7
			6.2	620	27.1	11.46	191.0	15.6	18.0
			6.9	690	27.7	12.08	201.4	15.7	18.1
● Dk. Brown 803610	○ 53 Dk. Blue	● Dk. Blue 833500	-	-	-	-	-	-	-
			5.5	550	27.1	11.86	197.7	16.1	18.6
			6.2	620	27.7	12.58	209.6	16.3	18.9
			6.9	690	28.3	13.24	220.6	16.5	19.0

G84B NOZZLES



G85B NOZZLES



LOW-ANGLE NOZZLES**



** Low-angle nozzles reduce radius by 15%

G85B NOZZLE PERFORMANCE DATA

Nozzle Set			Pressure		Radius	Flow		Precip mm/hr	
			bar	kPa	m	m ³ /hr	l/min	■	▲
● Orange 803603	○ 10 Lt. Green	● Dk. Green 315312	3.4	340	13.1	1.86	31.0	10.8	12.5
			4.1	410	13.4	2.23	37.1	12.4	14.3
			4.5	450	13.7	2.29	38.2	12.2	14.1
			-	-	-	-	-	-	-
● Orange 803603	○ 13 Lt. Blue	● White 315314	3.4	340	14.6	2.66	44.3	12.4	14.3
			4.1	410	15.2	2.91	48.5	12.5	14.5
			4.5	450	15.5	3.04	50.7	12.6	14.5
			-	-	-	-	-	-	-
● Orange 803603	○ 15 White	● White 315314	3.4	340	15.9	3.02	50.3	12.0	13.9
			4.1	410	16.2	3.34	55.6	12.8	14.8
			4.5	450	16.5	3.45	57.5	12.7	14.7
			-	-	-	-	-	-	-
● Orange 803603	○ 18 Orange	● Lt. Green 315313	3.4	340	16.8	3.79	63.2	13.5	15.6
			4.1	410	17.4	4.04	67.4	13.4	15.5
			4.5	450	17.7	4.13	68.9	13.2	15.3
			-	-	-	-	-	-	-
● Orange 803603	○ 20 Tan	● Lt. Green 315313	3.4	340	17.7	4.18	69.7	13.4	15.4
			4.1	410	18.3	4.45	74.2	13.3	15.4
			4.5	450	18.6	4.66	77.6	13.5	15.6
			4.8	480	18.6	4.88	81.4	14.1	16.3
5.5	550	18.9	5.13	85.6	14.4	16.6			
● Orange 803603	○ 23 Green	● Lt. Green 315313	3.4	340	18.6	4.78	79.6	13.8	16.0
			4.1	410	19.2	5.18	86.3	14.0	16.2
			4.5	450	19.8	5.43	90.5	13.8	16.0
			4.8	480	20.1	5.86	97.7	14.5	16.7
5.5	550	20.4	6.34	105.6	15.2	17.5			
● Red 803602	○ 25 Blue	● Green 315310	4.5	450	21.0	6.68	111.3	15.1	17.4
			4.8	480	21.3	6.92	115.3	15.2	17.6
			5.5	550	21.6	7.37	122.8	15.7	18.2
			6.2	620	21.9	7.77	129.5	16.1	18.6
6.9	690	22.3	8.25	137.4	16.7	19.2			
● Red 803602	○ 33 Grey	● Green 315310	-	-	-	-	-	-	-
			5.5	550	22.3	7.83	130.4	15.8	18.3
			6.2	620	22.6	8.34	138.9	16.4	18.9
			6.9	690	23.2	8.75	145.7	16.3	18.8
● Red 803602	○ 38 Red	● Green 315310	-	-	-	-	-	-	-
			5.5	550	24.1	8.94	149.0	15.4	17.8
			6.2	620	24.1	9.36	156.0	16.1	18.6
			6.9	690	24.4	9.75	162.4	16.4	18.9
● Red 803602	○ 43 Dk. Brown	● Green 315310	-	-	-	-	-	-	-
			5.5	550	24.4	9.88	164.7	16.6	19.2
			6.2	620	24.7	10.54	175.6	17.3	20.0
			6.9	690	25.3	11.06	184.3	17.3	20.0
● Dk. Red 803601	○ 48 Dk. Green	● Dk. Green 315312	-	-	-	-	-	-	-
			5.5	550	25.9	11.20	186.6	16.7	19.3
			6.2	620	26.2	11.86	197.6	17.3	19.9
			6.9	690	26.8	12.43	207.1	17.3	19.9
● Dk. Red 803601	○ 53 Dk. Blue	● Dk. Green 315312	-	-	-	-	-	-	-
			5.5	550	27.1	11.98	199.7	16.3	18.8
			6.2	620	27.4	12.54	209.0	16.7	19.2
			6.9	690	27.7	13.06	217.7	17.0	19.6

● = Nozzle plug P/N 315300 installed in the back side of the nozzle housing.

* Preliminary performance data.

B SERIES

Models: **G70B & G75B**
 Radius: **14.3 to 22.9 m**
 Flow: **1.75 to 7.66 m³/hr; 29.1 to 127.6 l/min**

FEATURES

- Models:
 - G70B: Full circle
 - G75B: Full/Part circle (50° to 360°)
- QuickCheck™ arc mechanism (G75B)
- QuickSet-360 arc mechanism (G75B)
- Nozzle choices:
 - G70B: 6 standard trajectory (25°)
 - G75B: 9 standard trajectory (25°)
- Nozzle range:
 - G70B: #15 to #28
 - G75B: #8 to #28
- Exclusive PressurePort™ nozzle technology
- Water lubricated gear-drive
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- G70B
 - Radius: 16.2 to 22.9 m
 - Discharge rate: 2.95 to 7.66 m³/hr; 49.2 to 127.6 l/min
 - Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- G75B
 - Radius: 14.3 to 21.6 m
 - Discharge rate: 1.75 to 7.34 m³/hr; 29.1 to 122.3 l/min
 - Pressure range: 2.8 to 6.9 bar; 280 to 690 kPa
- All B Series rotors are pressure rated at 10 bars; 1,000 kPa



G70B
 Pop-up height: 8 cm
 Overall height: 23 cm
 Flange diameter: 12 cm
 Female Inlet: 1/4" ACME



G75B
 Pop-up height: 8 cm
 Overall height: 23 cm
 Flange diameter: 12cm
 Female Inlet: 1/4" ACME

G70B & G75B - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Valve Options	3 Nozzle	4 Options
G70 = Full Circle	B = Block Rotor with Check Valve	25 = Installed G70 Nozzle * * Available in SSU model only SSU = #25 Includes nozzle pack	S = SSU * * Standard Stocking Unit
G75 = Full/Part Circle, 50° - 360° Arc Range	B = Block Rotor with Check Valve	25 = Installed G75 Nozzle ** ** Available in SSU model only SSU = #25 Includes nozzle pack	S = SSU * * Standard Stocking Unit


Example:
G70 - B - 25 - S = G70 full circle block rotor, installed #25 nozzle with nozzle pack, standard stocking unit model

G70B NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
15 ● Grey	3.4	340	16.2	2.95	49.2	11.3	13.1
	4.1	410	16.5	3.20	53.4	11.8	13.7
	4.5	450	16.8	3.36	56.0	12.0	13.8
	4.8	480	17.1	3.52	58.7	12.1	14.0
	5.5	550	17.7	3.70	61.7	11.8	13.7
18 ● Red	3.4	340	17.7	3.23	53.8	10.3	11.9
	4.1	410	18.0	3.61	60.2	11.2	12.9
	4.5	450	18.3	3.70	61.7	11.1	12.8
	4.8	480	18.3	3.84	64.0	11.5	13.3
	5.5	550	18.6	4.04	67.4	11.7	13.5
20 ● Dk. Brown	3.4	340	18.6	4.27	71.2	12.4	14.3
	4.1	410	18.9	4.45	74.2	12.5	14.4
	4.5	450	19.2	4.66	77.6	12.6	14.6
	4.8	480	19.5	5.00	83.3	13.1	15.2
	5.5	550	19.5	5.32	88.6	14.0	16.1
23 ● Dk. Green	3.4	340	19.2	4.57	76.1	12.4	14.3
	4.1	410	19.8	4.77	79.5	12.2	14.0
	4.5	450	19.8	4.97	82.9	12.7	14.6
	4.8	480	20.1	5.32	88.6	13.1	15.2
	5.5	550	20.4	5.66	94.3	13.6	15.7
25 ● Dk. Blue	3.4	340	19.8	4.95	82.5	12.6	14.6
	4.1	410	20.4	5.11	85.2	12.3	14.1
	4.5	450	20.4	5.36	89.3	12.9	14.8
	4.8	480	21.0	5.75	95.8	13.0	15.0
	5.5	550	21.6	6.11	101.8	13.0	15.1
28 ● Black	4.8	480	21.6	6.38	106.4	13.6	15.7
	5.5	550	21.6	6.79	113.2	14.5	16.7
	6.2	620	22.3	7.22	120.4	14.6	16.8
	6.9	690	22.9	7.66	127.6	14.6	16.9

* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

G75B NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
8 ● Lt. Brown	2.8	280	14.3	1.75	29.1	8.5	9.8
	3.4	340	14.9	1.89	31.4	8.5	9.8
	4.1	410	15.2	2.09	34.8	9.0	10.4
	4.5	450	15.2	2.16	36.0	9.3	10.7
	4.8	480	15.5	2.25	37.5	9.3	10.7
10 ● Lt. Green	3.4	340	16.2	2.48	41.3	9.5	11.0
	4.1	410	16.5	2.73	45.4	10.1	11.6
	4.5	450	16.5	2.84	47.3	10.5	12.1
	4.8	480	16.8	2.98	49.6	10.6	12.2
	5.5	550	17.1	3.25	54.1	11.1	12.9
13 ● Lt. Blue	3.4	340	16.8	2.54	42.4	9.1	10.5
	4.1	410	17.1	2.79	46.6	9.6	11.1
	4.5	450	17.1	2.91	48.5	10.0	11.5
	4.8	480	17.4	3.02	50.3	10.0	11.6
	5.5	550	17.4	3.25	54.1	10.8	12.4
15 ● Grey	3.4	340	17.4	3.04	50.7	10.1	11.6
	4.1	410	17.7	3.25	54.1	10.4	12.0
	4.5	450	18.0	3.36	56.0	10.4	12.0
	4.8	480	18.0	3.48	57.9	10.7	12.4
	5.5	550	18.3	3.73	62.1	11.2	12.9
18 ● Red	3.4	340	18.3	3.29	54.9	9.8	11.4
	4.1	410	18.6	3.57	59.4	10.3	11.9
	4.5	450	18.6	3.70	61.7	10.7	12.4
	4.8	480	18.9	3.84	64.0	10.7	12.4
	5.5	550	19.2	4.13	68.9	11.2	12.9
20 ● Dk. Brown	4.1	410	18.9	4.04	67.4	11.3	13.1
	4.5	450	18.9	4.13	68.9	11.6	13.4
	4.8	480	19.2	4.36	72.7	11.8	13.7
	5.5	550	19.5	4.66	77.6	12.2	14.1
	6.2	620	19.8	4.95	82.5	12.6	14.6
23 ● Dk. Green	4.1	410	19.5	4.97	82.9	13.1	15.1
	4.5	450	19.8	4.86	81.0	12.4	14.3
	4.8	480	19.8	5.36	89.3	13.7	15.8
	5.5	550	20.1	5.82	96.9	14.4	16.6
	6.2	620	20.4	6.13	102.2	14.7	17.0
25 ● Dk. Blue	4.1	410	19.8	5.34	89.0	13.6	15.7
	4.5	450	19.8	5.63	93.9	14.4	16.6
	4.8	480	20.4	5.82	96.9	13.9	16.1
	5.5	550	21.0	6.20	103.3	14.0	16.2
	6.2	620	21.6	6.59	109.8	14.1	16.2
28 ● Black	4.8	480	20.1	6.11	101.8	15.1	17.4
	5.5	550	20.7	6.56	109.4	15.3	17.6
	6.2	620	21.3	6.95	115.8	15.3	17.6
	6.9	690	21.6	7.34	122.3	15.7	18.1

G70B & G75B NOZZLES



G70B



G75B

B SERIES

Model: **G35B**
 Radius: **5.5 to 15.2 m**
 Flow: **0.43 to 2.91 m³/hr; 7.2 to 48.5 l/min**

FEATURES

- Model: G35B: Full/Part Circle (50° - 360°)
- QuickCheck™ arc mechanism
- QuickSet-360 arc mechanism
- Nozzle choices:
 - 8 multi-trajectory 15°-25°
- Nozzle range:
 - #2 to #12
- Water lubricated gear-drive
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- Radius: 5.5 to 15.2 m
- Flow: 0.43 to 2.91m³/hr; 7.2 to 48.5 l/min
- Pressure range: 2.8 to 4.5 bar; 280 to 450 kPa
- All B Series rotors are pressure rated at 10 bar; 1,000 kPa




G35B
 Pop-up height: 8 cm
 Overall height: 23 cm
 Flange diameter: 12 cm
 Female Inlet: 1/4" ACME

G35B - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Valve Options	3 Nozzle	4 Options*
G35 = Full/Part Circle 50° to 360°	B = Block rotor with check valve	6 = Installed G35 Nozzle* * Available in SSU model only SSU = #6 Includes nozzle rack	S = SSU* * Standard Stocking Unit

Example:
 G35 - B - 6 - S = G35 full/part circle block rotor, installed #6 nozzle with nozzle rack, standard stocking unit model

G835 NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
2 ● Yellow	2.8	280	5.5	0.43	7.2	14.3	16.6
	3.4	340	6.1	0.48	7.9	12.8	14.8
	4.1	410	6.7	0.55	9.1	12.1	14.0
	4.5	450	7.0	0.59	9.8	12.0	13.9
3 ● Yellow	2.8	280	7.0	0.68	11.4	13.9	16.0
	3.4	340	7.6	0.73	21.1	12.5	14.5
	4.1	410	8.2	0.80	13.2	11.7	13.6
	4.5	450	8.5	0.82	13.6	11.2	13.0
4 ● Yellow	2.8	280	7.6	0.89	14.8	15.3	17.6
	3.4	340	8.5	0.93	15.5	12.8	14.8
	4.1	410	9.1	1.00	16.7	12.0	13.8
	4.5	450	9.4	1.04	17.4	11.7	13.5
5 ● Yellow	2.8	280	8.8	1.07	17.8	13.7	15.8
	3.4	340	9.8	1.14	18.9	11.9	13.8
	4.1	410	10.1	1.20	20.1	11.9	13.7
	4.5	450	10.7	1.23	20.4	10.8	12.4
6 ● Yellow	2.8	280	9.8	1.36	22.7	14.3	16.5
	3.4	340	10.7	1.43	23.8	12.6	14.5
	4.1	410	11.3	1.50	25.0	11.8	13.6
	4.5	450	11.9	1.54	25.7	10.9	12.6
8 ● Yellow	2.8	280	11.0	1.77	29.5	14.7	17.0
	3.4	340	11.9	1.82	30.3	12.9	14.8
	4.1	410	12.8	1.89	31.4	11.5	13.3
	4.5	450	13.1	1.93	32.2	11.2	13.0
10 ● Yellow	2.8	280	11.9	2.20	36.7	15.6	18.0
	3.4	340	13.1	2.29	38.2	13.4	15.4
	4.1	410	13.7	2.34	39.0	12.4	14.4
	4.5	450	14.3	2.39	39.7	11.6	13.4
12 ● Yellow	2.8	280	13.4	2.73	45.4	15.2	17.5
	3.4	340	14.3	2.77	46.2	13.5	15.6
	4.1	410	14.6	2.84	47.3	13.3	15.3
	4.5	450	15.2	2.91	48.5	12.5	14.5



HQSLRC Quick Coupler
with HSJ-1 SnapLok™ equipped swing joint

Introducing Hunter's new full line of HSJ heavy-duty swing joints with configurations for every need and every project. There is even a version specifically designed for quick coupler applications. The SnapLok outlet on HSJ-1 models come equipped with accommodations for both rebar and pipe stabilisation, as well as heavy-duty brass outlet threads with a unique anti-rotation locking feature.

See the HSJ swing joints on page 177



* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

ROTOR ACCESSORIES

HOSE-SWIVEL ADAPTERS

Models

- Hose swivel adapter for G90 and G900 Series (fits ¾" & 1" hose) P/N G90HS100
- Hose swivel adapter for G800 Series (fits ¾" & 1" hose) P/N G800HS100



Hose Swivel Adapters

RUBBER COVER KITS

Models

- G990 rubber cover kit (date codes 06/11 & prior only) P/N 473800
- G995 rubber cover kit (also G990 date codes 07/11 & after) P/N 473900



Rubber Cover Kit