FEATURES

- Model: G835: Full/Part circle (50° to 360°)
- QuickCheck™ arc mechanism
- QuickSet-360 arc mechanism
- Nozzle choices: 8 multi-trajectory (15° to 25°)
- Nozzle range: #2 to #12
- · Water lubricated gear-drive
- ► All TTS advanced features
- ► Decoder-In-Head (DIH) capable

OPERATING SPECIFICATIONS

- Radius: 5.5 to 15.2 m
- Flow: 0.43 to 2.91 m³/hr; 7.2 to 48.5 l/min
- Pressure range: 2.8 to 4.5 bar; 280 to 450 kPa
- All TTS rotors are pressure rated at 10 bar; 1,000 kPa

OPTIONS

- C Check-O-Matic checks up to 8 m in elevation change and readily converts to Normally-Open Hydraulic with through the top connections
- D Decoder Valve-In-Head with all "E" specifications below*
- DD Two-station Decoder Valve-In-Head with all "E" specifications below*
- E Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 210 mA (370 mA inrush) 50Hz; 190 mA (350 mA inrush) 60Hz solenoid with captive plunger and internal downstream bleed
- * All DIH rotors include two IBM DBRY-6 splices for connection to the 2-wire path. See page 184 for critical recommendations on grounding DIH rotors.
- ▶ = TTS and DIH Advanced Features on pages 154 and 156



G835C

Pop-up height: 8 cm Overall height: 30 cm Flange diameter: 18 cm Female Inlet: 1½" ACME



G835E

Pop-up height: 8 cm Overall height: 30 cm Flange diameter: 18 cm Female Inlet: 1½" ACME

G835 - SPECIFICATION BUILDER: ORDER 1+2+3+4+5

1 Model	2 Valve Options	3 Nozzle	4 Regulation*	5 Options
G835 = Full/Part Circle 50 to 360°	C = Check-O-Matic *	6 = Installed G835 Nozzle *	P5 = 50 PSI	S = SSU *
	D = Decoder Valve-in-Head includes 8-nozzle rack	includes 8-nozzle rack	P6 = 65 PSI	
	E = Electric Valve-in-Head			
	* Converts to N.O. Hydraulic Valve-in-Head	* SSU = #6	* SSU = P5	* Standard Stocking Unit

Examples:

G835E-6-P5-S = G835 full/part-circle electric valve-in-head, installed #6 nozzle, 50 PSI regulation, standard stocking unit model

G835 NOZZLE PERFORMANCE DATA*

Nozzle	Pres	sure	Radius	Fle	ow	Precip	mm/hr
	bar	kPa	m	m³/hr	l/min		
	2.8	280	5.5	0.43	7.2	14.3	16.6
2 •	3.4	340	6.1	0.48	7.9	12.8	14.8
Yellow	4.1	410	6.7	0.55	9.1	12.1	14.0
	4.5	450	7.0	0.59	9.8	12.0	13.9
2	2.8	280	7.0	0.68	11.4	13.9	16.0
3	3.4	340	7.6	0.73	21.1	12.5	14.5
Yellow	4.1	410	8.2	0.80	13.2	11.7	13.6
	4.5	450	8.5	0.82	13.6	11.2	13.0
4	2.8	280	7.6	0.89	14.8	15.3	17.6
4	3.4	340	8.5	0.93	15.5	12.8	14.8
Yellow	4.1	410	9.1	1.00	16.7	12.0	13.8
	4.5	450	9.4	1.04	17.4	11.7	13.5
-	2.8	280	8.8	1.07	17.8	13.7	15.8
5	3.4	340	9.8	1.14	18.9	11.9	13.8
Yellow	4.1	410	10.1	1.20	20.1	11.9	13.7
	4.5	450	10.7	1.23	20.4	10.8	12.4
C •	2.8	280	9.8	1.36	22.7	14.3	16.5
6	3.4	340	10.7	1.43	23.8	12.6	14.5
Yellow	4.1	410	11.3	1.50	25.0	11.8	13.6
	4.5	450	11.9	1.54	25.7	10.9	12.6
0 0	2.8	280	11.0	1.77	29.5	14.7	17.0
8	3.4	340	11.9	1.82	30.3	12.9	14.8
Yellow	4.1	410	12.8	1.89	31.4	11.5	13.3
	4.5	450	13.1	1.93	32.2	11.2	13.0
10 0	2.8	280	11.9	2.20	36.7	15.6	18.0
10 •	3.4	340	13.1	2.29	38.2	13.4	15.4
Yellow	4.1	410	13.7	2.34	39.0	12.4	14.4
	4.5	450	14.3	2.39	39.7	11.6	13.4
12 0	2.8	280	13.4	2.73	45.4	15.2	17.5
12 •	3.4	340	14.3	2.77	46.2	13.5	15.6
Yellow	4.1	410	14.6	2.84	47.3	13.3	15.3
	4.5	450	15.2	2.91	48.5	12.5	14.5

 $^{^{\}ast}$ Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.





G835 NOZZLES



QuickSet-360

With Hunter's QuickCheck arc mechanism and patented QuickSet-360 non-reversing full-circle feature in a variable arc rotor, adjustments are fast, easy and more flexible than ever before. Now available on all B Series and G800 Series adjustable arc rotors.