PRO-SPRAY®

Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm Inlet: 1/2"

FEATURES

- Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm
- · Compatible with all female threaded nozzles
- No side inlet (NSI) version available in 15 cm and 30 cm
- · Innovative directional flush plug design
- · Warranty period: 5 years
- ► Co-molded wiper seal
- ▶ Heavy-duty spring
- ► Industry's strongest spray body
- ► Innovative seal design
- ► Pro-Spray check valve

OPERATING SPECIFICATIONS

• Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa

FACTORY INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation)
- · Check valve available on 10 cm, 15 cm, 30 cm
- Reclaimed water ID cap

USER INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation; P/N 437400)
- Reclaimed water ID cap (P/N 458520)
- Snap-on reclaimed cover (P/N PROSRCCAP)
- = Advanced Feature descriptions on page 58



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps.

PRO-SPRAY - SPECIFICATION BUILDER: ORDER 1 + 2



Model

PROS-00 = Shrub Adapter

PROS-02 = 5 cm Pop-up

PROS-03 = 7.5 cm Pop-up

PROS-04 = 10 cm Pop-up

PROS-06 = 15 cm Pop-up

PROS-06-NSI = 15 cm Pop-up (no side inlet)

PROS-12 = 30 cm Pop-up

PROS-12-NSI = 30 cm Pop-up (no side inlet)

Options

(blank) = No option

CV = Factory-installed drain check valve (Pop-up models only, 15 cm and 30 cm models ordered as CV will come as no side inlet)

R = Factory-installed reclaimed body cap (shrub molded in purple)



Examples:

PROS-04 = 10 cm Pop-up

PROS-06 - CV = 15 cm Pop-up, drain check valve

PROS-12 - CV - R = 30 cm Pop-up, drain check valve, reclaimed body cap



PROS-00

Retracted height: 4 cm Inlet size: 1/2"



PROS-02

Retracted height: 10 cm Pop-up height: 5 cm Exposed diameter: 5.7 cm Inlet size: 1/2"



PROS-03

Retracted height: 12.5 cm Pop-up height: 7.5 cm Exposed diameter: 5.7 cm Inlet size: 1/2"



PROS-04

Retracted height: 15.5 cm Pop-up height: 10 cm Exposed diameter: 5.7 cm Inlet size: 1/2"



[A] **PROS-06**

[B] PROS-06-NSI

Retracted height: 22.5 cm Pop-up height: 15 cm Exposed diameter: 5.7 cm Inlet size: 1/21



[A] PROS-12

[B] PROS-12-NSI

Retracted height: 41 cm Pop-up height: 30 cm Exposed diameter: 5.7 cm Inlet size: 1/21