

# ROAM XL

Range: **Up to 3 km**  
Type: **Remote**

## FEATURES

- Works with Hunter X-Core®, Pro-C®, PCC, I-Core® and ACC controllers through a SmartPort® connection
- Up to 3 km (line of sight) range for remote manual operation of Hunter irrigation systems
- 128 different programmable addresses
- Display shows remaining battery life
- Programmable run times: 1 to 90 minutes
- Large LCD display, push-button operation
- Run manual watering cycles without modifying regular program
- Rugged plastic carrying case included
- Warranty period: 3 years

## REMOTE SPECIFICATION

- Transmitter power source: 4 AAA batteries included
- Receiver power source: 24 VAC, from controller through a SmartPort connector
- System operating frequency: 27 MHz band
- SmartPort connector can be mounted up to 15 m (max.) from controller (use ROAM-SCWH shielded cable wiring harness)
- FCC approved: No FCC licence required

\* Not available in all countries.



**Roam XL**  
(w/o antenna)  
Height: 16 cm  
Width: 8 cm  
Depth: 3 cm

CONTROLLERS

ROAM XL	
Model	Description
ROAMXL-KIT	Transmitter, receiver, SmartPort wiring harness, 4 AAA batteries and plastic carrying case included
ROAMXL-R	Receiver unit (SmartPort wiring harness included)
ROAMXL-TR	Handheld transmitter, and 4 AAA batteries included

OPTIONS	
Model	Description
258200	Wall Mount Bracket for SmartPort
ROAMXL-CASE	Plastic carrying case
ROAM-WH	SmartPort wiring harness (length: 1.8 m)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 7.6 m)



**SmartPort**  
Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter remote.



**Wall Mount Bracket for SmartPort**  
P/N 258200