

ROAM

Range: **Up to 300 m**
Type: **Remote**

FEATURES

- Works with Hunter X-Core®, Pro-C®, PCC, I-Core® and ACC controllers through a SmartPort® connection
- 128 programmable addresses for use of multiple Roam remotes in the same neighborhood
- Run manual watering cycles without modifying regular program
- Programmable run times: 1 to 90 minutes
- Range: 300 m (line of sight)
- Warranty period: 2 years

REMOTE SPECIFICATION

- Transmitter power source: 4 AAA batteries included
- Receiver power source: 24 VAC, from controller through a SmartPort connector
- System operating frequency: 433 MHz band
- SmartPort connector can be mounted up to 15 m (max.) from controller (use ROAM-SCWH shielded cable wiring harness)
- FCC approved: No FCC licence required



Transmitter and Receiver

Height: 18 cm
Width: 6 cm
Depth: 3 cm



SmartPort

Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter remote.

Wall Mount Bracket for SmartPort

P/N 258200

ROAM	
Model	Description
ROAM-KIT	Transmitter, receiver, SmartPort wiring harness, and 4 AAA batteries included
ROAM-R	Receiver unit
ROAM-TR	Transmitter unit, and 4 AAA batteries included

OPTIONS	
Model	Description
ROAM-WH	SmartPort wiring harness (length: 1.8 m)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 7.6 m)
258200	Wall mount bracket for SmartPort

CONTROLLERS