



NOTE INLET PIPE LENGTH OF SENSOR MUST BE MIN. 10X PIPE DIA. STRAIGHT, CLEAN RUN OF PIPE, NO FITTINGS OR TURNS. OUTLET PIPE LENGTH OF SENSOR MUST BE MIN. 5X PIPE DIA. OF STRAIGHT CLEAN RUN OF PIPE, NO FITTINGS OR TURNS.

XX

FLOW—CLICK ON IMMS

SCALE: 1:8

Number® IRRIGATION DETAIL

- 1

MODEL FLOW—CLICK IMMS—XXX
- 2

MODEL FCT—XXX (SEE CHART TO SIZE)
- 3

MIN. 18/4 WIRE TO SITE INTERFACE.
MAXIMUM WIRE DISTANCE RUN OF 328m
- 4

STANDARD VALVE BOX
- 5

FINISH GRADE
- 6

MAIN LINE PIPE
- 7

MASTER VALVE
- FCT FITTING SELECTION

FCT100	32mm	SCH. 40
FCT150	50mm	SCH. 40
FCT158	50mm	SCH. 80
FCT200	63mm	SCH. 40
FCT208	63mm	SCH. 80
FCT300	90mm	SCH. 40
FCT308	90mm	SCH. 80
FCT400	110mm	SCH. 40