

# MP ROTATOR®

Radius: 2.5 to 10.7 m

## FEATURES

- Matched precipitation at any arc or radius setting
- Radius can be reduced up to 25% on all models
- Easy arc adjustment
- Colour-coded for easy identification
- Double-pop feature keeps dirt and debris out of nozzle
- Removable filter screen ensures hassle-free service
- Avoid runoff with low precipitation rate
- Wind-resistant multi-stream technology
- High distribution uniformity
- ▶ Automatic matched precipitation
- ▶ Double-pop

## OPERATING SPECIFICATIONS

- Recommended operating pressure: 2.8 bar; 280 kPa

## OPTIONS

- Pair with Pro-Spray® PRS40 to achieve pressure regulation at the head of 2.8 bar; 280 kPa
- Adding “HT” will specify male threaded nozzles

▶ = Advanced Feature descriptions on page 40

### MP1000 2.5 to 4.6 m radius



**MP1000-90**  
90° to 210°



**MP1000-210**  
210° to 270°



**MP1000-360**  
360°

### MP2000 4 to 6.4 m radius



**MP2000-90**  
90° to 210°



**MP2000-210**  
210° to 270°



**MP2000-360**  
360°

### MP-3000 6.7 to 9.1 m radius



**MP3000-90**  
90° to 210°



**MP3000-210**  
210° to 270°



**MP3000-360**  
360°

### MP3500 9.4 to 10.7 m radius



**MP3500-90**  
90° to 210°

### MP ROTATOR – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
<b>MP1000-90</b> = 2.5 to 4.6 m radius, adjustable from 90° to 210°	<b>(blank)</b> = No option  <b>HT</b> = Male threaded version <i>(Not available in 3500)</i>
<b>MP1000-210</b> = 2.5 to 4.6 m radius, adjustable from 210° to 270°	
<b>MP1000-360</b> = 2.5 to 4.6 m radius, 360°	
<b>MP2000-90</b> = 4.0 to 6.4 m radius, adjustable from 90° to 210°	
<b>MP2000-210</b> = 4.0 to 6.4 m radius, adjustable from 210° to 270°	
<b>MP2000-360</b> = 4.0 to 6.4 m radius, 360°	
<b>MP3000-90</b> = 6.7 to 9.1 m radius, adjustable from 90° to 210°	
<b>MP3000-210</b> = 6.7 to 9.1 m radius, adjustable from 210° to 270°	
<b>MP3000-360</b> = 6.7 to 9.1 m radius, 360°	
<b>MP3500-90</b> = 9.4 to 10.7 m radius, adjustable from 90° to 210°	
<b>MPLCS515</b> = Left corner strip, 1.5 m to 4.6 m	
<b>MPRC515</b> = Right corner strip, 1.5 m to 4.6 m	
<b>MPSS530</b> = Side strip, 1.5 m to 9.1 m	
<b>MPCORNER</b> = 2.5 to 4.5 m radius, adjustable from 45° to 105°	

#### Examples:

**MP1000-210** = 2.5 to 4.6 m radius, adjustable from 210° to 270°  
**PROS-06-PRS40-CV-MP2000-90** = 15 cm pop-up regulated at 2.8 bar, drain check valve, with MP2000-90