

# FILTER REGULATOR

System: **Regulation and Filtration, All in One Component**

## FEATURES

- Factory-assembled and water-tested
- Highest quality components (stainless steel filter screen, standard flush cap, top-of-the-line regulator)
- Wide flow range to cover most micro irrigation applications
- Warranty period: 2 years

## HFR-100-075, HFR-075

- Pressure regulation: 25 or 40 PSI
- Flow: 0.5 to 15 GPM (30 to 900 GPH)
- Operating pressure: 20 to 120 PSI
- Operating temperature: up to 120° F
- 150 mesh; 100 microns stainless steel screen



**HFR-100-075-25**

**HFR-100-075-40**

Height: 7"  
Width: 2¾"  
Length: 6¼"  
1" inlet x ¾" outlet



**HFR-075-25**

**HFR-075-40**

Height: 7"  
Width: 2¾"  
Length: 6¼"  
¾" inlet x ¾" outlet



**HY-100, HY-100-75,**

**HY-075**

Height: 6"  
Width: 3"  
Length: 5"



**HY-151**

Height: 11"  
Width: 4.5"  
Length: 8"

## HUNTER FILTER REGULATOR

Model	Description
HFR-075-25	¾" inlet x ¾" outlet, regulated at 25 PSI
HFR-075-40	¾" inlet x ¾" outlet, regulated at 40 PSI
HFR-100-075-25	1" inlet x ¾" outlet, regulated at 25 PSI
HFR-100-075-40	1" inlet x ¾" outlet, regulated at 40 PSI

## HUNTER Y-FILTER

- Filter HY-100 1" Male NPT
- Filter HY-100-075 1" Male NPT inlet x ¾" Male outlet
- Filter HY-075 ¾" Male
  - Filter only (no regulation)
  - Extra large 150 mesh; 100 microns stainless steel screen
- Filter HY-151 1½" Male NPT
  - Filter only (no regulation)
  - Extra large 120 mesh; 125 microns stainless steel screen

MICRO