

MLD

MINI LANDSCAPE DRIPLINE

Flow: **0.4-0.85 GPH**
 Surface Irrigation: **Short Runs and Planters**
 Fittings: **All ¼" barb fittings**

FEATURES

- Perfect for short runs and planters
- 100' and 250' rolls
- 6" or 12" emitter spacing
- 250' rolls uncoil from the inside of the roll for easy, no-hassle dispensing
- Offered in both brown or black
- Use with standard ¼" barb fittings
- Warranty period: 2 years

OPERATING SPECIFICATIONS

- 0.250" outside diameter x 0.175" inside diameter
- Operating pressure: 10-40 PSI
- Materials: LLDPE
- Minimum bending radius: 12"
- Minimum filtration: 150 mesh; 100 microns

► = Flow chart available on page 169



MLD

MLD Installed



MLD - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1	Model	2	Spacing	3	Length	4	Options
MLD-05		06	= 6"	100	= 100'	(blank)	BL = Black
		12	= 12"	250	= 250'		= Brown

Example:

MLD-05 - 12 - 250 = 0.5 GPH mini landscape dripline with 12" spacing in a 250' roll, brown

MAXIMUM RUN LENGTH

Pressure (PSI)	Emitter Spacing (in.)	Run Length (ft.)
25.0	6"	15'
25.0	12"	30'
40.0	6"	15'
40.0	12"	30'

Notes: Run lengths based on maintaining consistent flows.

ECO-INDICATOR

Uses: **Drip System Indicator**

FEATURES

- Visible yellow stem indicates system is in operation
- Attach to polyethylene or PVC via ½" MPT connection
- Requires 12 PSI to pop-up
- Commercial-grade body and stem
- Warranty: 2 years

OPERATING SPECIFICATIONS

- Operating pressure range: 0-60 PSI
- Indication of system operation: 12-60 PSI



ECO-ID

Pair with Eco-Mat® and Eco-Wrap® subsurface systems.