

MULTI-PORT EMITTERS

Pressure Compensating Flow: **0.5, 1.0, 2.0, 4.0 GPH**

FEATURES

- Unused ports may be closed using vinyl emitter caps
- Pressure-compensating
- Perfect for mixed plantings or series of shrubs
- Flows are color-coded to match other Hunter emitters
- ½" threaded
- Commercial-grade for all PVC systems
- Manifold available
- Warranty period: 2 years

OPERATING SPECIFICATIONS

- Recommended Pressure: 5 to 65 PSI
- Minimum Filtration: 150 mesh; 100 microns

MULTI-PORT EMITTER MODEL CHART

	Model	Flow (GPH)
● Blue	MPE-05	0.5
● Black	MPE-10	1.0
● Red	MPE-20	2.0
● Tan	MPE-40	4.0
● Gray	MPM-050	N/A



Multi-Port Emitter



MULTI-PORT MANIFOLD

(MPM-050)

Unrestricted flow through outlets as indicated by gray color. Use with ¼" distribution tubing and a barbed emitter at the end (Available in ½" FPT). Allows water to be directed to as many as six different locations.

EMITTER CAPS

(MPE-CAPS)

Plugs unused ¼" barbed emitter outlets. Use with Hunter Multi-Port Emitters.



RIGID RISER

Surface Irrigation: **Height Adjustment**

FEATURES

- For rugged system designs
- Accepts 10-32 threaded components
- Perfect for annual flower beds and planters
- Inlet configurations: ½" FPT, ¼" barb, or blank
- HDPE construction
- Warranty period: 1 year

RIGID RISER MODEL CHART

Model	Description
RR12	12" rigid riser
RR12-T	12" rigid riser with ½" threaded base
RR12-B	12" rigid riser with ¼" barb base
RR18	18" rigid riser
RR18-T	18" rigid riser with ½" threaded base
RR18-B	18" rigid riser with ¼" barb base



12" RIGID RISER



18" RIGID RISER